



AIRPORT EQUIPMENT SERVICES PTE. LTD.

41 Kallang Pudding Road, #03-10 Golden Wheel Building,
Singapore 349316 Phone: (65) 65421160 Fax: (65) 65421160
Email: aessg@singnet.com.sg Website: www.aessg.com

(Business Registration No: 199400661M)



标准技术参数 Main Technical Specifications

| | | | | | | |
|-------------------|---|---------------|--------------|-------|-------|------|
| 性能 | 牵引车型号 Model | | TE20 | TE25 | TE30 | |
| | 牵引力 Drawbar pull | KN | 21 | 22 | 23 | |
| | 牵引重量(干燥混凝土地面) Towed weight at dry even concrete surface | kg | 20000 | 25000 | 30000 | |
| | 行驶速度 Travel speed | 空载 No load | km/h | 20 | 20 | 20 |
| | | 满载 Full load | km/h | 12 | 11 | 10 |
| | 最大爬坡度(空载) Max. grade ability | % | 30 | | | |
| 尺寸 | 总长(含牵引栓) Overall length | mm | 3150 | | | |
| | 总宽 Overall width | mm | 1440 | | | |
| | 总高 Overall height | mm | 1450 | | | |
| | 轴距 Wheelbase | mm | 1850 | | | |
| | 前轮距 Front tread | mm | 1240 | | | |
| | 后轮距 Rear tread | mm | 1190 | | | |
| | 最小转弯半径 Min. turning radius | mm | 3250 | | | |
| | 牵引栓中心高度 Center height coupler | mm | 305/405 | | | |
| | 最小离地间隙 Min. ground clearance | mm | 120 | | | |
| 轮胎尺寸 Tire size | 前轮 Frond | mm | 6.50-10 10PR | | | |
| | 后轮 Rear | mm | 7.00-12 12PR | | | |
| 重量 | 整机重量 Truck weight | kg | 3700 | 3800 | 3900 | |
| | 空载轴荷 Weight distribution | 前轴 Frond axle | kg | 1700 | 1700 | 1700 |
| | | 后轴 Rear axle | kg | 2000 | 2100 | 2200 |
| | 蓄电池电压/容量 Battery | V/AH | 80/690 | | | |
| | 电机功率 Motor power | Kw | 28.7 | | | |

尺寸 Overall dimensions

