



AIRPORT EQUIPMENT SERVICES PTE. LTD.

41 Kallang Pudding Road, #03-10 Golden Wheel Building,
Singapore 349316 Phone: (65) 65421160 Fax: (65) 65421160
Email: aessg@singnet.com.sg Website: www.aessg.com

(Business Registration No: 199400661M)

KLB20/KLB30 牵引车 **基本参数**

	Mode(型号)	KLB20	KLB30
Performance (性能)	Maximum load capacity (负载能力)	kg 2000	3000
	Weight (with battery) (含电池重量)	kg 580	580
Dimensions (尺寸)	Overall length of frame (整车长度)	L mm1375	1375
	Overall width of frame (整车宽度)	B mm735	735
	Handle height (手柄高度)	H2 mm1485	1485
	Min frounf height (最小离地间隙)	S mm66	66
	Pull bolt height (牵引栓高度)	H3 mm100-268	100-268
	Overall height of frame (整车高度)	H mm1290	1290
	Minimum turning radius (最小转弯半径)	Wamm1220	1220
Tire (轮胎)	Front wheel (承载轮)	mm160*50	160*50
	Drive wheel (驱动轮)	mm250*80	250*80
	Caster wheel (平衡轮)	mm75*32	75*32
	Driver wheel material (驱动轮类型)	Polyurethane(聚氨酯)	
Electrical components (动力形式)	Front and caster wheel (承载轮和平衡轮类型)	Rubber (橡胶)	
	Drive motor type (驱动电机类型)	AC series motor (交流电机)	
	Rated output (功率)	kw 1.5	1.5
	battery (电池)	Voltage (电压)	V 24
Capacity (容量)		AH 210	210

