



AIRPORT EQUIPMENT SERVICES PTE. LTD.

41 Kallang Pudding Road, #03-10 Golden Wheel Building,
 Singapore 349316 Phone: (65) 65421160 Fax: (65) 65421160
 Email: aessg@singnet.com.sg Website: www.aessg.com

(Business Registration No: 199400661M)

LT QD20 / 25 / 30



标准技术参数 Main Technical Specifications

性能	牵引车型号 Model code			QD20	QD25	QD30
		牵引力 drawbar pull		KN	19	21
能	牵引重量(干燥混凝土地面) towed weight at dry even concrete surface		kg	20000	25000	30000
	行驶速度 Travel speed	空载 No load	km/h	28	28	28
		满载 Full load	km/h	15	13	11
	最大爬坡度 Max. gradeability	空载 No load	%	30	30	30
尺寸	总长(包括牵引栓) Overall length (with coupler) A		mm	2980	2995	3020
	总宽 Overall width B		mm	1440	1440	1435
	总高 Overall height (不含驾驶室) C		mm	1380	1380	1400
	轴距 Wheelbase D		mm	1900	1900	1900
	前轮距 Front tread G		mm	1220	1220	1220
	后轮距 Rear tread H		mm	1160	1160	1160
	最小转弯半径 Min. turning radius 外 Outer I		mm	3100	3100	3050
	牵引栓中心高度 Center height coupler L		mm	305/405	305/405	304.8/405
	最小离地间隙 Min. ground clearance M		mm	150	150	150
轮胎	轮胎尺寸 Tire size	前轮 Front	mm	6.00-9	6.00-9	6.00-9
		后轮 Rear	mm	7.00-12	7.00-12	7.00-12
重量	整机重量(空载) Truck weight(No load)		kg	3500	3600	3700
	空载轴荷 Weight distribution	前轴 Front axle	kg	1360	1380	1400
		后轴 Rear axle	kg	2140	2220	2300
蓄电池(电压、容量) Battery		V/AH	80V/690AH	80V/690AH	80V/690AH	
电机功率 Motor Power		KW	28.7	28.7	28.7	