

MT1211 Covered Mail Trolley



长 Length	3920mm	自重 Weight	750kg
宽 Width	1700mm	载重量 Loading capacity	2000kg
高 Height	2000mm	最大时速 Max speed	25km/h
工作平台高度 Working surface height	560mm	最小转弯半径 Min turning radius	≤3500mm

Specifications:

- ➔ Suitable for loading and unloading of luggage, package and bulk cargo, can move swiftly on all kinds of ground conditions in any places.
- ➔ Main chassis uses 8# international channel steel, the frame body is welded from 40 × 30 rectangular steel pipes. The box skin are made of corrugation color steel plates;
- ➔ The roof are arc design, can quickly remove rainwater from it, even in summer stormy seasons;
- ➔ Two-door-opening design at both sides, making the loading and unloading of cargo much more convenient. The self designed connected sliding door roller, make the doors easy to open and close, also with inhibiting and holding devices. The sliding doors on both sides have safety locks;
- ➔ Tow bar is welded from high quality seamless heavy wall steel pipes, and several trolleys can be towed together;
- ➔ The rear hitch is our patented product, its patent no. is China :201020032933.6. Three protection design, spring stressing, clamping position and slot, hitch self-weight, to avoid any unlocked accident when being towed. The inserted bar with self locked device is made of φ35mm high quality round steel bar, pull up the bar from clamping slot and rotate it, That's easy operation for connection and disconnection.;
- ➔ Antirust and surface painting after removing rust and sanding the entire trolley. The color of surface painting is in accordance with the clients' order