



AIRPORT EQUIPMENT SERVICES PTE. LTD.

41 Kallang Pudding Road, #03-10 Golden Wheel Building,
Singapore 349316 Phone: (65) 65421160 Fax: (65) 65421160
Email: aessg@singnet.com.sg Website: www.aessg.com

(Business Registration No: 199400661M)

**THREE BOTTLE NITROGEN CART
(MODEL NO : NC 299)**



SPECIFICATION

:-

Loading Capability	:	Three N2 Cylinder
Overall Length	:	3130 mm Handle Extended
Overall Width	:	1530 mm
Overall Height	:	1170 mm Handle Up
Weight	:	250 kgs (Appr.)
Wheel	:	400 - 8 Pneumatic Tyre
Parking Brake	:	Mechanical Brake System
Max. Towing Speed	:	25 km/h
Charging System	:-	
High Pressure	:	Inlet 6,000 psi & Outlet 25 - 4,000 psi
Low Pressure	:	Inlet 5,000 psi & Outlet 0 - 250 psi
Outlet Hose	:	30 ft Length (not include adaptor)

SPECIFICATION OF NITROGEN CHARGING KIT

<u>Particulars</u>	<u>Qty</u>
Brand : TESCOM	
* About unit is certified to be used for high pressure NITROGEN gas application, control cabinet with 2 outlet pressure range 0 - 4000 psi and 0-250 psi respectively one (1) each.	
1) " Tescom " High Pressure Regulator (Inlet 4000 psi & Outlet 25 - 4000 psi)	1
2) " Tescom " Low Pressure Regulator (Inlet 4000 psi & Outlet 0 - 250 psi)	1
3) 1/4" x 1 Meter Inlet Hose	3
4) 1/4" x 9 Meter Outlet Hose	2
5) " Wika " 2" Dia. Inlet Gauge (0 - 4000 psi)	4
6) " Wika " 2" Dia. Outlet Gauge (0 - 400 psi)	1
7) 1/4" Stainless Steel Needle Valve	3
8) 1/4" Air Safety Relief Valve	1
9) Fitting (NPT)	1 set
10) Brass Manifold	1
11) Pressure Gauge Calibration Certificate (Certify by SIME-SIRIM Malaysia)	1 ea

*** This charging kit is not included charging adaptor**