



# AIRPORT EQUIPMENT SERVICES PTE. LTD.

41 Kallang Pudding Road, #03-10 Golden Wheel Building,  
Singapore 349316 Phone: (65) 65421160 Fax: (65) 65421160  
Email: aessg@singnet.com.sg Website: www.aessg.com

(Business Registration No: 199400661M)

## TK-SP60 Catering Truck



The TK-SP60 catering truck is built upon reliable ISUZU commercial chassis featuring with reliable performance. It is in full compliance with CAAC and international standards, such as, IATA AHM 910, IATA AHM 913, IATA AHM 915, IATA AHM 927 and MH/T 6016-1999 etc.

### Dimensions

Overall Dimensions	9500*2500*3760 mm
Wheelbase	5550 mm
Front Wheel Tread	1960 mm
Rear Wheel Tread	1855 mm
Minimum Turning Radius	9400 mm
Ground Clearance	200 mm
Gross Vehicle Weight	15750 kg

### Performance Data

Maximum Speed	45 km/h
Service Range	2200-5800 mm
Vanbody Load Capacity	4000 KG
Platform Load Capacity	800 KG

### Applicable Aircraft:

A300, A310, A320, A340, BAe146, B727, B737, B747, B757, B767 etc

## Standard Features

ISUZU Commercial Chassis  
ISUZU 4KH1-TC Diesel Engine Euro III Emission  
Hydraulic Power Assisted Steering  
Leaf Spring Suspensions with Shock Absorber  
6 Forward 1 Reverse Manual Transmission  
  
Insulated Vanbody  
  
Standard Lightings  
  
Adequate Warning Lights/Indicators

## Safety Features

Emergency Stop Button  
Emergency Platform Descend  
Anti-collision Sensor  
Interlock to prevent moving when vanbody lifted  
Interlock to prevent vanbody lifting when stabilizers not fully extended  
Interlock to prevent vanbody descending when stabilizers not fully retracted  
Interlock to prevent stabilizers retraction when vanbody is not fully descended  
Interlock to prevent hydraulic movements unless parking brake engaged  
Emergency Manual Pump

## Highlights

Adopting ISUZU commercial chassis, featuring with good dependability and good spare parts commonality.

Equipped with various of interlocks and protections, providing the most safe operation.

## Diagram & Details

