

AIRPORT EQUIPMENT SERVICES PTE. LTD.

41 Kallang Pudding Road, #03-10 Golden Wheel Building, Singapore 349316 Phone: (65) 65421160 Fax: (65) 65421160 Email: aessg@singnet.com.sg Website: www.aessg.com

(Business Registration No: 199400661M)

ZTSH2T06 Baggage Trolley



1. Description

- Suitable for luggage and bulk cargo use. Adjustable waterproof curtain and sliding doors on both sides to protect luggage and cargo from inclement weather.
- Steering Mechanism: Front axle mounted steering for small turning radius
- Rear Tow Hitch: Secure self-locking rear hitch for connection of a train of 4 baggage trolleys.
- Tyres: Heavy Duty, wear resistant solid tyres
- Braking System: Tow bar brake actuated on front wheels when tow bar is in fully downward position.
- ☐ Materials: Mild Steel Sheet (3 mm thick) on both sides & roof top of box. Mild Steel tubes (40x40x1.5mm(tk) for frame structure.
- Surface Treatment: Anti-rust primer and 2 layers of finished paint are applied after shot blasting. Buyer needs to inform the colour codes for corporate identity.

Dimensions:

dimensions:	
Description	Two sides opening with sliding doors with canvas and
	stainless steel nettings.
Dimensions: L x W x H	4220mm (with tow bar) \times 1575 mm $_{X}$ 1929mm
Platform Height	560mm (from ground level to loading platform)
Tyres	4.00-8
Dead Weight	≥700Kg
Load Capacity	2000 Kg
Max Towing Speed	25km/h
Min Turning Radius	≤4500mm